

ADTL

Downtime Monitor Tower Light

**SIGNAWORKS**
www.signaworks.com



MODEL TYPES

- ADTS > Tower Light Indicator Incandescent
- ADTL > Tower Light Indicator LED
- ADTXP > Pilot Light and Strobe Light Indicator XP (22 mm)
- ADTLP > Strobe Light Indicator LP (77 mm)

FEATURES

- > Visual indicator for downtime condition
- > Incandescent or LED tower light or strobe signals downtime
- > Timer Tracks time per occurrence or accumulates time for shift
- > Manual, Automatic, or keyed time reset
- > use free spreadsheet document for manual data logging & analysis
- > 110VAC via 8 foot 3 prong power cord
- > Continuous, flashing, or audible alarms

ACCESORIES AND OPTIONS

- > Flashing (F) and Buzzer (B) or both (Z) at the end of the cycle
- > Extended cable between switch and light box
- > RS485 link for logging events to pc
- > Link monitor to supervisor, maintenance, engineering, etc
- > Optional Ethernet data logging to collect time stamp or event data - Free PC Software
- > Optional Wireless communication to bingo board or flatscreen
- > Ethernet Data Logging available with RJ45 connector
- > Wireless Inputs or Outputs available for remote signals or data logging



ORDERING INFORMATION

- | | |
|-------------------|---|
| Model Type | > ADTS, ADTL, ADTXP, ADTLP |
| Voltage Number of | > 12, 24 VDC 110-220 VAC |
| Lights Colors | > 1, 2, 3, 4, 5 |
| Number of Timers | > Red, Amber, Green, Blue, Clear |
| Ordering Example | > 1, 2, 3, 4, 5 (or more) |
| | > Ordering Example: ADTL-110-3-2 (LED, 110VAC, 3 Light (Red, Amber, Green), 2 Timers) |

- Add to the Prefix for additional features:
- F: Continuous and flashing light
 - B: Continuous light with audible alarm
 - Z: Continuous and flashing light with audible alarm